

# Stretch Vinyl Self Adhesive 270µ

Stretch Vinyl Self Adhesive 270µ has a water resistant coating that allows beautiful imaging for many indoor and outdoor applications. It features a re-positional adhesive layer and can be used where uneven surfaces need to be covered. It can be stretched allowing it to follow every contour of the surface it is applied to.

## Compatibility overview

Compatible with Waterbased inks.



Water  
based



(Eco)  
solvent



Latex



UV-cure

## Physical characteristics

- Thickness without layer and adhesive: 90µ
- Thickness product: 270µ

## Features

- Smooth surface
- Re-positionable
- Easy to mount
- Water fastness
- Optimal stretch
- Durable
- Easy handling
- Indoor/Outdoor

## Applications

- Signs & Displays
- Decoration
- Trade show graphics

## Shelf life and environment aspects

The shelf life of this media is 1 year under normal conditions (10°C – 35°C at a relative humidity 30% - 75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place in its original packaging.

### Lamination

To add surface protection from dirt and abrasion a pressure sensitive laminate is recommended. A laminate also protects against gas-fading. Waiting for about 4 hours before laminating is recommended. For mounting on a board encapsulating a safe edge of 5-6mm around the image is recommended.

Because of the great variety of substrates and application methods the installer must examine the suitability of the media for each application. Sentec assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect special, incidental damages or consequential loss.

### Important:

Before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.

### Sentec International BV

Pascallaan 36  
8218 NJ Lelystad  
T: +31 (0)320 26 78 26  
F: +31 (0)320 26 78 28

[www.sentecinternational.com](http://www.sentecinternational.com)  
[info@sentecinternational.com](mailto:info@sentecinternational.com)