

Expose Backlit Film Gloss Quickdry 205µ

Expose Backlit Film Gloss Quickdry 205µ is a thick, bright, white polyester backlit film with a glossy surface and excellent scratch resistance. Viewing with reflected or transmitted light gives outstanding image contrast and colour gamut. It is a cost-effective solution for premium quality backlit displays.

Compatibility overview

Compatible with (Eco)Solvent, Latex, and UV-cure inks.



Water
based



(Eco)
solvent



Latex



UV-cure

Physical characteristics

- Base material: Polyester
- Surface: Glossy
- Weight: 285g/m²
- Thickness: 205µ

Product code	Product size	Core diameter
813519-1372	1372mm x 30m	3 inch

Custom sizes are available with minimum order quantities required

Features

- Short dry-time
- Scratch resistant surface
- Cold laminates recommended
- Recyclable
- Excellent dimensional stability
- Tear resistant
- Water resistance
- Allows high ink load

Applications

- High quality backlit signage
- Kiosks
- POS displays
- Trade show graphics
- Indoor banner

Shelf life and environment aspects

The shelf life of this media is 1 year under normal conditions (10°C – 35°C at a relative humidity 30% - 75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place in its original packaging.

Sentec International BV
Pascallaan 36
8218 NJ Lelystad
T: +31 (0)320 26 78 26
F: +31 (0)320 26 78 28

www.sentecinternational.com
info@sentecinternational.com

Rev. November 2017

Important:

Before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.