



Product description

DM Magnetic PET Film 300 μ is an easy-to-use magnetic polyester based film that can be easily and quickly installed by untrained personnel. It can be applied to almost any steel-based surface to meet the demands for changeable graphics. It is durable and reduces the lifecycle cost for signage.

Print compatibility

-  (Eco)Solvent inks
-  Latex inks
-  UV-cure inks
-  Screenprint

Shelf life and environment aspects

The shelf life of this media is 1 year under normal conditions (10°C – 35°C at a relative humidity 30% - 75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place in its original packaging.

Important:
Before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.

Physical characteristics

Surface: Satin
Print side: White polyester
Base material: Flexible magnet

Thickness: 300 μ
Weight: 635 g/m²

Magnetic force: 8-10 g/m²
Guaranteed magnetic force: \geq 8 g/m²

Features

Flexible polyester base
Adheres to steel-based surfaces
PVC-free
Indoor and static outdoor use
Easy to install and remove
Reduces the life-cycle cost for signage

Certified for HP Latex inks
(more information: <https://www.printos.com/ml/#/medialocator>)

Applications

Retail advertising
Trade show graphics
Interior decoration
Wall graphics