## DreamScape® WallWrap Specification Sheet v:040419



Product Name:

## DreamScape Brilliant, Caviar, Classic, Ravello

Description:Peel and stick, re-positionable wallcovering product with unique textures; 2-4 times thicker than other wraps to hide wall imperfections.Construction:Polymeric vinyl 3-ply with fabric supportPackaging:Each roll is meticulously packaged in a re-usable tube. No splices, no creases, no flat spots for printer efficiency.Ink Compatibility:UV curable, Solvent and Latex ink systems

Availability:

Availability.					
			US	Metric	
	Roll Sizes:	Widths:	54"	1.37m	
		Lengths:	25yds, 50yds, 100yds	30m, 50m, 100m	
		Trial Rolls:	27″x15′	.686m x 4.57m	
Weight:					
			US	Metric	
	Product Weight:	Product Weight WITH Lining:	20.5 oz. per lineal yard (13.7 oz. per square yard)	464.5 g/m <sup>2</sup>	
		Product Weight WITHOUT Lining:	15 oz. per lineal yard (10 oz. per square yard)	339.1 g/m <sup>2</sup>	
Thickness:					
			US	Metric	
		Ravello:	0.013 in.	0.33 mm	
	Product Thickness	Caviar:	0.013 in.	0.33 mm	
		Classic:	0.011.	0.28 mm	
		Brilliant:	0.013 in.	0.33 mm	
	Cold Crack Resistance @ 20F - no change				
	Heat Aging 7 days @ 158F - no change				
Adhesive Properties	re Properties Acrylic Based- Fire Retardant;Non-Permanent.   Low Tack and Peel - can be repositioned with no adhesive residue on removal   Adheres to almost any smooth surface   Tested on dry wall, glass, metal, wood paneling, and display board   Shrinkage - Edge shrinkage of 1mm to 2mm is possible in the first 30 days   A 0.5" seam overlap is recommended   For best results follow the DreamScape Wall Wrap Install Instructions.				
Removability:	When applied properly on a suitable surface, the adhesive will maintain it's standard release for 2 years. Beyond 2 years, the bond strength with the wall surface may gradually increase.				
Durability and Longevity:	This product is recommended for indoor use.				
	Outdoor life of unprinted material - 3 years				
	Indoor life of unprinted material - 10 years				
Application:	Wallwrap has been tested on drywall and many other smooth clean surfaces.				
	Drywall requires a sealed surface with a level 4 or 5 finish. Uncured paints and primers can result in poor adhesion. Due to the variability of surfaces, sealers, paints and environmental conditions, DreamScape does not accept claims for application or removal failures. It is the user's obligation to test and verify suitability prior to application.				
Warranty:	5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at				
6	http://www.dreamscapewalls.				
Comments:	*Meets or exceeds requirement	its for flame spread, sm	oke developed and flashover.		

DreamScape – a division of Roysons Corp. • 40 Vanderhoof Ave. • Rockaway, NJ 07866